

## AMENDMENTS TO THE CLAIMS

1. (CURRENTLY AMENDED). A method for representing a motion for two blocks, comprising the steps of:

(A) exchanging a particular value of a plurality of values with a memory, each of said values defining which of said two blocks use which of a plurality of motion vectors based upon one of a plurality of prediction types; wherein (1) said prediction types include (i) a first prediction type for of said two block using a first reference picture list, ~~and~~ (ii) a second prediction type for of said two blocks using a second reference picture list, (iii) a third prediction type of said two blocks using a bidirectional prediction and (iv) a fourth prediction type of said two blocks using an intra prediction and (2) said exchanging includes at least one of reading from said memory and writing to said memory; and

(B) representing said motion for said two blocks with a group comprising said particular value and up to all of said motion vectors, wherein said two blocks use a macroblock adaptive field/frame coding.

2. (CURRENTLY AMENDED) The method according to claim 1, wherein said group ~~comprises~~ has at most a plurality of bits that

is less than a maximum number of bits capable of representing each unique possibility for said motion vectors.

3. (CURRENTLY AMENDED) The method according to claim 1, wherein a first plurality of said motion vectors ~~for~~ corresponding to a first of said two blocks ~~are equal to~~ matches a second plurality of said motion vectors ~~for~~ corresponding to a second of said two blocks.

4. (PREVIOUSLY PRESENTED) The method according to claim 3, further comprising the step of:  
excluding said second plurality of said motion vectors from said group.

5. (ORIGINAL) The method according to claim 1, wherein said group includes at most two of said motion vectors.

6. (ORIGINAL) The method according to claim 5, wherein said particular value defines how many of said motion vectors are used by at least one of said two blocks.

7. (ORIGINAL) The method according to claim 1, wherein one of said values defines using none of said motion vectors.

8. (CURRENTLY AMENDED) The method according to claim 1, further comprising the step of:

using a list 0 prediction of said prediction types ~~for~~  
with said motion vectors, wherein (i) said motion vectors comprise  
5 two motion vectors and (ii) each of said two motion vectors is used  
for a different one of said two blocks.

9. (CURRENTLY AMENDED) The method according to claim 1, further comprising the step of:

using a list 1 prediction of said prediction types ~~for~~  
with said motion vectors, wherein (i) said motion vectors comprise  
5 two motion vectors and (ii) each of said two motion vectors is used  
for a different one of said two blocks.

10. (CURRENTLY AMENDED) The method according to claim 1,  
~~further comprising the step of:~~

~~using a~~ wherein under said bidirectional prediction of  
said prediction types, ~~for said motion vectors, wherein~~ each of  
5 said motion vectors is used for both of said two blocks.

11. (CURRENTLY AMENDED) The method according to claim 1,  
wherein step (B) comprises the sub-steps of:

generating said group with said particular value while  
above a predetermined standard level for a bitstream conveying said  
5 two macroblocks; and

generating said groups without said particular value  
while below said predetermined standard level for said bitstream.

12. (CURRENTLY AMENDED) The method according to claim 1,  
further comprising the steps of:

interpreting said motion vectors in said group based upon  
said particular value while above a predetermined standard level  
5 for a bitstream conveying said two macroblocks; and

using said motion vectors in said group independently of  
said particular value while below said predetermined standard level  
for said bitstream.

13. (CURRENTLY AMENDED) An apparatus comprising:

a memory; and

a circuit configured to (i) exchange a particular value  
of a plurality of values with said memory, each of said values  
5 defining which of two blocks use which of a plurality of motion  
vectors based upon one of a plurality of prediction types and (ii)  
represent a motion for said two blocks with a group comprising said  
particular value and up to all of said motion vectors, wherein (1)  
said prediction types include (a) a first prediction type for of

10    said two block using a first reference picture list, and (b) a  
second prediction type ~~for~~ of said two block using a second  
reference picture list, (iii) a third prediction type of said two  
block using a bidirectional prediction and (iv) a fourth prediction  
type of said two blocks using an intra prediction, (2) said  
15    exchange includes at least one of a read from said memory and a  
write to said memory, ~~wherein~~ and (3) said two blocks use a  
macroblock adaptive field/frame coding.

14.    (CURRENTLY AMENDED) The apparatus according to claim  
13, wherein said group ~~comprises~~ has at most a plurality of bits  
that is less than a maximum number of bits representing every  
unique possibility for said motion vectors.

15.    (ORIGINAL) The apparatus according to claim 13,  
wherein said group includes at most two of said motion vectors.

16.    (ORIGINAL) The apparatus according to claim 15,  
wherein said particular value defines how many of said motion  
vectors are used by at least one of said two blocks.

17.    (ORIGINAL) The apparatus according to claim 13,  
further comprising:

a coding circuit configured to encode said particular value within a bitstream.

18. (ORIGINAL) The apparatus according to claim 13, further comprising:

a decoder circuit configured to decode said particular value from a bitstream.

19. (CURRENTLY AMENDED) The apparatus according to claim 13, wherein:

a first of said values defines using none of said motion vectors;

5 a second of said values defines said first prediction type;

a third of said values defines said second prediction type; and

10 a fourth of said values defines a said bidirectional prediction type of ~~said prediction types~~.

20. (CURRENTLY AMENDED) An apparatus comprising:

means for storing a group; and

5 means for (i) exchanging a particular value of a plurality of values with said means for storing, each of said values defining which of two blocks use which of a plurality of

motion vectors based upon one of a plurality of prediction types and (ii) representing a motion for said two blocks with a group comprising said particular value and up to all of said motion vectors, wherein (1) said prediction types include (a) a first prediction type for of said two blocks using a first reference picture list, and (b) a second prediction type for of said two blocks using a second reference picture list, (c) a third prediction type of said two blocks using a bidirectional prediction and (d) a fourth prediction type of said two blocks using an intra prediction, (2) and said exchanging includes at least one of reading from said means for storing and writing to said means for storing and (3) said two blocks use a macroblock adaptive field/frame coding.

21. (PREVIOUSLY PRESENTED) A method for representing a motion for two blocks, comprising the steps of:

(A) generating a representation for said motion for said two blocks, said representation having less than a maximum number of bits capable of representing each possible combination of four motion vectors for said two blocks; and

(B) exchanging said representation with a memory, wherein (i) said exchanging includes at least one of reading from said memory and writing to said memory and (ii) said two blocks use a macroblock adaptive field/frame coding.

22. (CURRENTLY AMENDED) The method according to claim 21, wherein said representation comprises (i) a particular value of a plurality of values and (ii) up to all of said motion vectors a binary representation.

23. (CURRENTLY AMENDED) The method according to claim 21, wherein said representation is configured to accommodate (i) a first number of possible vectors for that could be expressed by a first of said motion vectors for corresponding to a first block of said two blocks, (ii) a second number of possible vectors for that could be expressed by a second of said motion vectors for corresponding to said first block, (iii) a third number of possible vectors for that could be expressed by a third of said motion vectors for corresponding to a second block of said two blocks and (iv) a fourth number of possible vectors for that could be expressed by a fourth of said motion vectors for corresponding to said second block.

24. (ORIGINAL) The method according to claim 23, wherein said presentation is less than a base 2 logarithm of a product of said first number, said second number, said third number and said fourth number rounded up to a nearest integer.



25. (CURRENTLY AMENDED) The method according to claim 21, wherein said representation is capable of representing up to two motion vectors ~~for~~ corresponding to each of said two blocks, each of said two motion vectors ~~for~~ corresponding to each of said two blocks can take on at least 67,108,864 unique values, and said representation uses fewer than 104 bits.